

# ACC 1834S3 微型三轴加速度计

## 产品规格书

### ACC 1834S3 Micro Triaxial Accelerometer

### Product Specification

|                              |   |
|------------------------------|---|
| 产品规格书-中文.....                | 1 |
| Product introduction-EN..... | 4 |

从此文件发布日期起，在此发表的是当前或者拟定的信息。由于我们会不断对产品进行改进和增加特征此出版物中的信息如有变动恕不另行通知。

From the date of this document's release, the information published here is current or proposed. As we will continuously improve and add features to our products, the information in this publication is subject to change without further notice.

最终版权所有 (c) 深圳市美格信测控技术有限公司

Copyright (c) Shenzhen MegaSig Measurement & Control Technology Company Limited

## 产品简介

---

### ACC 1834S3 微型三轴加速度计



美格信压电式加速度传感器，内部自带了电荷放大器，采用压电陶瓷材料制造的敏感元件使其具有良好的性能，能够在更极限的温度和更宽的测量范围内稳定运行。

IEPE压电式加速度传感器，采用1/4-28 UNF四芯线缆转BNC同轴线缆给传感器供给 2-10mA的恒流电源，而输出信号也由这同轴电缆输出，国际上通称ICP方式。

ACC 1834S3经常搭配MegaSig PM 6183等内置IEPE采集卡达到优秀测试效果。

## 功能特点

---

- IEPE供电三轴加速度计，整体采用钛合金材质，重量轻，体积小
- 整体采用剪切结构设计，抗干扰能力强，高稳定性
- 应用于多轴向振动测试分析，车辆、航空等研发及应用

## 规格参数


| 整体参数    |                    |             |
|---------|--------------------|-------------|
| 灵敏度     | 10mV/g (±10%)      |             |
| 测量范围    | ±500g              |             |
| 频率范围    | 1Hz-15kHz (±5%)    |             |
| 最大横向灵敏度 | ≤5%                |             |
| 幅值线性度   | ≤1%                |             |
| 宽频带分辨率  | 0.005grms          |             |
| 安装谐振频率  | >50kHz             |             |
| 冲击抵抗    | 2kg                |             |
| 工作电压范围  | +18 ~ +28V         |             |
| 工作电流范围  | +2 ~ +10mA (典型4mA) |             |
| 工作温度范围  | -40 ~ +120℃        |             |
| 输出电压峰值  | ≤6V                |             |
| 宽带噪声    | 0.005g             |             |
| 频谱噪声    | 10 Hz              | 350(μg/√Hz) |
|         | 100 Hz             | 70(μg/√Hz)  |
|         | 1000 Hz            | 30(μg/√Hz)  |
| 基座应变    | 0.001g/με          |             |
| 磁灵敏度    | 1.5g/T             |             |

## 机械结构

| 机械结构   |            |
|--------|------------|
| 敏感元件   | 压电陶瓷       |
| 壳体材料   | 钛合金        |
| 结构形式   | 剪切型        |
| 重量     | <3.5g      |
| 输出接口   | 1/4-28四芯插座 |
| 输出接口位置 | 侧端出线       |
| 安装接口   | M3内螺纹      |
| 附件     | 蜂蜡*1       |

机械尺寸

单位：mm



建议搭配使用线缆规格

| 型号   | 图片 | 说明                                                              |
|------|----|-----------------------------------------------------------------|
| 403A |    | 1/4-28UNF接头 转 3×BNC接头，外径2.4mm蓝色PVR材质线缆，三轴低噪声线缆，柔软性较高，耐95℃，可定制长度 |

在无深圳市美格信测控技术有限公司优先书面授权书前提下，此出版物任何一个部分不可通过任何形式进行复制、修改和翻译。对于非法复制、修改和翻译商业行为，将根据国家知识产权相关法律追求其法律责任。

## Product introduction

---



### Micro Triaxial Accelerometer

The MegaSig piezoelectric accelerometer features an internal charge amplifier. Its sensing element, made of piezoelectric ceramic material, delivers excellent performance, enabling stable operation under more extreme temperatures and across a wider measurement range.

The IEPE piezoelectric accelerometer utilizes a 1/4-28 UNF four-conductor to BNC coaxial cable. This cable supplies the sensor with a constant current power source of 2-10 mA, and also carries the output signal. This method is internationally known as ICP.

The ACC 1834S3, when paired with built-in IEPE acquisition cards such as the MegaSig PM 6183, often achieves outstanding testing results.

### Features

---

- IEPE-powered triaxial accelerometer, constructed entirely from titanium alloy, featuring lightweight and compact design
- Shear structure design throughout ensures strong anti-interference capability and high stability
- Applied in multi-axial vibration testing and analysis, as well as research, development, and applications in automotive, aerospace, and other fields

## Specification parameters


| Parameters                     |                            |                          |
|--------------------------------|----------------------------|--------------------------|
| Sensitivity                    | 10mV/g ( $\pm 10\%$ )      |                          |
| Measurement range              | $\pm 500g$                 |                          |
| Frequency range                | 1Hz-15kHz ( $\pm 5\%$ )    |                          |
| Maximum transverse sensitivity | $\leq 5\%$                 |                          |
| Amplitude linearity            | $\leq 1\%$                 |                          |
| Wide-band Resolution           | 0.005grms                  |                          |
| Mounting resonant frequency    | >50kHz                     |                          |
| Shock resistance               | 2kg                        |                          |
| Operating voltage range        | +18 ~ +28V                 |                          |
| Operating current range        | +2 ~ +10mA (typical 4mA) ) |                          |
| Operating temperature range    | -40 ~ +120°C               |                          |
| Peak output voltage            | $\leq 6V$                  |                          |
| Broadband noise                | 0.005g                     |                          |
| Spectral noise                 | 10 Hz                      | 350( $\mu g/\sqrt{Hz}$ ) |
|                                | 100 Hz                     | 70( $\mu g/\sqrt{Hz}$ )  |
|                                | 1000 Hz                    | 30( $\mu g/\sqrt{Hz}$ )  |
| Base strain                    | 0.001g/ $\mu\epsilon$      |                          |
| Magnetic sensitivity           | 1.5g/T                     |                          |

## Mechanical structure

| Mechanical structure      |                       |
|---------------------------|-----------------------|
| Sensitive element         | Piezoelectric ceramic |
| Shell material            | Titanium alloy        |
| Structure Type            | Shear Type            |
| Weight                    | <3.5g                 |
| Output Connector          | 1/4-28 4-Pin Socket   |
| Output connector position | Side-exit wiring      |
| Mounting interface        | M3 internal thread    |
| Accessories               | Beeswax *1            |

Mechanical Size

Unit: mm



Recommended cable specifications for matching use

| Model | Picture | Description                                                                                                                                                                                                  |
|-------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 403A  |         | 1/4-28UNF connector to 3×BNC connector, with an outer diameter of 2.4mm blue PVR material cable. It is a three-axis low-noise cable, featuring high flexibility, resistance to 95℃, and customizable length. |

Without the prior written authorization of Shenzhen MegaSig Measurement & Control Technology Company Limited, no part of this publication may be reproduced, modified or translated in any form. Legal liability will be pursued in accordance with the national laws on intellectual property rights for commercial activities involving illegal reproduction, modification or translation.